

LawMate AHD -TR10 Digital Wireless Transmitter and Receiver

FEATURES

- \cdot $\,$ AHD high-resolution digital wireless secure transmission/reception.
- · Suitable for private use where cabling is unsuitable or internet access is unavailable.
- · Lightweight, compact, and easy to use. No complex set up required.
- \cdot TX/RX frequency settings utilise automatic codec for secure operation.
- · Built-in high-capacity battery for portability. Extended operation with applied AC power.
- · Compatible with the BU-18AHD Camera or other compatible AHD cameras.
- Signal reception compatible with the PV-1000AHD or other compatible AHD DVR for recording and archivng.
- · Tested transmission range: 500 meters in an open line of sight.

	SPECIFICATION: TX10
	SPECIFICATION, TATO
INTERNAL MODULE	Internal 2.4G Digital Module
OUTPUT POWER	10-IIdBm / Standard
T / R FREQUENCY	2408 - 2478Mhz
Tx CHANNEL	19 Channels
DYNAMIC RATE	Around 200/s
RF BAND WIDTH	12 Mbps
MODULATION	QPSK/16QAM
LATENCY	Including AHD Convertion. Overall Latency Around 100ms
TX VIDEO IN SIGNAL FORMAT	AHD @1080P/720P
ANT GAIN	3dB
WORKING RANGE	Open Terrain 500m
POWER INPUT	DC 5V
POWER CONSUMPTION	External Camera: 900mA-950mA
	No Camera: 370-400mA
	Transmitting Static Images: 940-1050mA
	Transmitting Dynamic Images: 1.2A-1.4A
CHARGING TIME	I.SA 4000mA Battery 4H
BATTERY INPUT	DC 3.7V / 4000 mA LI battery
BATTERY LIFETIME	Continunous TX:220Min
DIMENSION	88x 25 x 23mm
WEIGHT	95g

SPECIFICATION: RX10	
INTERNAL MODU LE	Internal 2.4G Digital Module
T / R FREQUENCY	2408 - 2478Mhz
RX CHANNEL	19 Channels
RX VIDEO OUTPUT SIGNAL FORMAT	AHD @1080P/720P
ANT GAIN	3dB
VIDEO OUTPUT IMPEDANCE	75Ω, Typ
POWER INPUT	DC5V
POWER CONSUMPTION	No TV Output: 370mA-400mA
	Transmitting images: 450-500mA
CHARGING TIME	15A 4000mA Battery 4H
BATTERY INPUT	DC 3.7V / 4000 mA LI Battery
BATTERY LIFETIME	Continuous TX: 450 Min
DIMENSION	88x 25 x 23mm
WEIGHT	95g

^{*} This product is for Law Enforcement and Home Security Use Only







